

HTPD 2018



Contribution ID : 64

Type : not specified

10.49 A Non-Invasive Method of Measuring the Height of Liquid-Metal Surface Waves

Wednesday, 18 April 2018 10:31 (120)

Liquid-metal plasma facing components (LM-PFC's) could provide fusion reactors with improved tritium breeding capabilities, enhanced power removal, and 'self-healing' interior surfaces that are immune to both radiation damage and thermal stress. During reactor operation, fast-moving, smooth-flowing LM-PFC surfaces are preferred since surface waves may cause non-uniform heating of the LM-PFC and splashing of liquid metal could upset or extinguish the plasma. However, surface waves and instabilities on LM-PFC's can be caused by a number of different factors including interactions with tokamak surfaces (e.g. diagnostic ports), magnetic transients, and interactions with the 'plasma wind'. Identifying the location and measuring the amplitude of liquid-metal waves during reactor operation is an important step towards minimizing and controlling them. Therefore, a non-invasive electromagnetic diagnostic has been developed to quantify localized surface waves in LM-PFC's. This low-cost diagnostic is installed beneath the substrate that the liquid-metal flows so it is insulated from thermal transients. This paper provides details on the design, construction, and operation of the new diagnostic. Experimental data is compared to numerical results.

Primary author(s) : HVASTA, Michael (Princeton University)

Co-author(s) : KOLEMEN, Egemen (Princeton University); FISHER, Adam (Princeton University)

Presenter(s) : HVASTA, Michael (Princeton University); KOLEMEN, Egemen (Princeton University); FISHER, Adam (Princeton University)

Session Classification : Session #10, Wednesday Morning Poster Session