

HTPD 2018



Contribution ID : 97

Type : not specified

12.22 Initial operation results of NE213 scintillation detector for the time-resolved triton burnup measurements in KSTAR

Wednesday, 18 April 2018 20:31 (120)

For the purpose of time-resolved triton burnup measurements in the KSTAR deuterium plasmas, an NE213 liquid scintillation detector has been installed and operated during the 2017 KSTAR campaign. The detector is composed of a 2-inch diameter NE213 scintillator and a photomultiplier tube (PMT). The PMT pulse signal is processed by the data acquisition system of which the field programmable gate array circuit and the pulse processing software can discriminate the pulse signals from gamma-ray and neutron. In order to achieve a good neutron and gamma-ray discrimination performance, the maximum count rate was retained under 10^5 counts per seconds by shielding the scintillator with 5 cm thick lead blocks and 20 cm thick borated polyethylene blocks. To determine an appropriate threshold level of 14 MeV neutron signal resulting from triton burnup, the NE213 scintillation detector has been calibrated by the 2.5 MeV neutron source in NFRI and the Intense 14 MeV Neutron Source Facility, OKTAVIAN, of Osaka University, Japan. The operation result is compared with the parameters related to the triton birth and confinement characteristics of KSTAR deuterium plasmas, e.g. 2.5 MeV neutron emission rate, plasma current, and electron Coulomb collision time.

Primary author(s) : JO, Jungmin (Department of Energy System Engineering, Seoul National University)

Co-author(s) : CHEON, MunSeong; KIM, Junghee (National Fusion Research Institute); ISOBE, Mitsutaka (National Institute for Fusion Science, National Institutes of Natural Sciences); OGAWA, Kunihiro (National Institute for Fusion Science, National Institutes of Natural Sciences); NISHITANI, Takeo (National Institute for Fusion Science, National Institutes of Natural Sciences); PARK, Seungil (National Fusion Research Institute); MURATA, Isao (Division of Sustainable Energy and Environmental Engineering, Graduate School of Engineering, Osaka University); CHUNG, Kyoung-Jae (Department of Energy System Engineering, Seoul National University); HWANG, Yong-Seok (Department of Energy System Engineering, Seoul National University)

Presenter(s) : JO, Jungmin (Department of Energy System Engineering, Seoul National University); CHEON, MunSeong; KIM, Junghee (National Fusion Research Institute); ISOBE, Mitsutaka (National Institute for Fusion Science, National Institutes of Natural Sciences); OGAWA, Kunihiro (National Institute for Fusion Science, National Institutes of Natural Sciences); NISHITANI, Takeo (National Institute for Fusion Science, National Institutes of Natural Sciences); PARK, Seungil (National Fusion Research Institute); MURATA, Isao (Division of Sustainable Energy and Environmental Engineering, Graduate School of Engineering, Osaka University); CHUNG, Kyoung-Jae (Department of Energy System Engineering, Seoul National University); HWANG, Yong-Seok (Department of Energy System Engineering, Seoul National University)

Session Classification : Session #12, Wednesday Night Poster Session