

HTPD 2018



Contribution ID : 129

Type : not specified

## 12.54 Development of Phase Contrast Imaging on HL-2A Tokamak

Wednesday, 18 April 2018 20:31 (120)

Phase contrast imaging (PCI) has been recently developed on HL-2A tokamak. In this article we will present the construction and calibration of this diagnostic. The system is able to diagnose the chord integral density fluctuations by measuring the phase shift of a CO<sub>2</sub> laser beam with a wavelength of 10.6  $\mu\text{m}$  when passing through the plasma region vertically. There are 32 channels of HgCdTe detector array, covering the plasma region of  $0.625 < r/a < 0.7$ . This diagnostic is designed to detect plasma density fluctuations with the maximum wavenumber of 15 /cm. The designed wavenumber resolution is 2 /cm restricted by the window size and the time resolution can reach 2  $\mu\text{s}$ . The broad normalized wavenumber  $k_{\text{ps}}$  ranging from 0.2 to 3 makes it suitable for turbulence measurement. The error field caused by magnetization of a large steel-made optical platform of the system on the top of HL-2A is evaluated for safety reasons. Sound waves are used to calibrate PCI diagnostic. The signal series in different PCI channels show a pronounced modulation of incident laser beam by the sound wave. Frequency-wavenumber spectrum is achieved. Calibrations by sound waves with different frequencies exhibit a maximal wavenumber response of 12 /cm.

Primary author(s) : GONG, Shaobo (University of Science and Technology of China)

Presenter(s) : GONG, Shaobo (University of Science and Technology of China)

Session Classification : Session #12, Wednesday Night Poster Session