

Abstract Submitted  
for the DPP01 Meeting of  
The American Physical Society

Sorting Category: 5.6.3 (Experimental/Observational)

**Stabilization of Resistive Wall Modes in DIII-D<sup>1</sup>**

E.J. STRAIT, M.S. CHU, R.J. LA HAYE, J.T. SCOVILLE, A.D. TURNBULL, General Atomics, J. BIALEK, A.M. GAROFALO, G.A. NAVRATIL, Columbia U., L.C. JOHNSON, M. OKABAYASHI, PPPL — Experiments in DIII-D show that a resistive wall mode (RWM) can be stabilized at high beta by active feedback control or by plasma rotation. Feedback may assist in rotational stabilization by counteracting the marginally stable plasma's resonant response to n=1 error fields ("error field amplification"<sup>2</sup>), which would otherwise slow the plasma rotation. However, direct feedback stabilization of the RWM is also observed in experiments with reduced plasma rotation. Comparison of new sensors installed in the DIII-D vessel this year shows that feedback control of the RWM is improved with sensors closer to the plasma and further improved with poloidal field sensors (which do not couple to the active coils), in qualitative agreement with model predictions. Beta values approaching twice the no-wall ideal MHD stability limit have been sustained by feedback control in a rotating plasma, and by rotation alone.

<sup>1</sup>Work supported by the US DOE under Contracts DE-AC03-99ER54463, DE-FG02-89ER53297, and DE-AC02-76CH03073.

<sup>2</sup>A.H. Boozer, Phys. Rev. Lett. **86**, 5059 (2001).

Prefer Oral Session  
 Prefer Poster Session

E.J. Strait  
strait@fusion.gat.com  
General Atomics

Date submitted: July 20, 2001

Electronic form version 1.4