

Abstract Submitted for the Forty-Seventh Annual  
Meeting  
Division of Plasma Physics  
October 24–28, 2005, Denver, Colorado

Category Number and Subject:

☐ Theory      ☒ Experiment

**ELM Trigger Model: Sheath Breakdown Caused by Thermoelectrically Driven SOL Current in ELM Precursor Phase,\*** H. Takahashi, E.D. Fredrickson, *Princeton Plasma Physics Laboratory*, M.J. Schaffer, N.H. Brooks, T.E. Evans, G.L. Jackson, L.L. Lao, *GA*, M.E. Austin, *U. Texas*, J.G. Watkins, *SNL* – The breakdown of the sheath at the interface of the SOL plasma and divertor tiles, through which thermoelectrically driven scrape-off-layer current (SOLC) flowing along open field lines enters the tokamak structure, is investigated [1] in DIII-D as a possibly causal element in the ELM triggering process. Sheath breakdown may occur when the ion saturation current density ( $j_{\text{sat}}$ ) at the sheath falls to the SOLC current density, increasing the potential drop across the sheath. The limiting  $j_{\text{sat}}$  varies cyclically through the ELM cycle, reaching a minimum, as the SOL density is pumped out, just before the ELM crash. The increased SOL current following breakdown may contribute toward destabilizing MHD modes. Evidence for sheath breakdown is sought from measurement by the SOLC and Langmuir probe diagnostics.

[1] H. Takahashi, et al., EPS Paper 4.018, Tarragona, Spain (2005).

\*Work supported by U.S. DOE under DE-AC02-76CH03073, DE-FC02-04ER54698, DE-FG023-97ER54415 and DE-AC04-94AL85000.

☐ Oral      ☒ Poster