

**Abstract Submitted for the 54th Annual Meeting  
Division of Plasma Physics  
October 29 through November 2, 2012  
Providence, Rhode Island**

Category Number and Subject: 5.6.2. DIII-D Tokamak

Theory       Experiment

**Assessment of Error Field Control with the ‘n=1 Coil’,\* C. Paz-Soldan, *ORISE*; E.J. Strait, R.J. La Haye, R.J. Buttery, *General Atomics*; J.M. Hanson, *Columbia University*; M.J. Lanctot, *LLNL* –** Small deviations from the nominally axisymmetric field of a tokamak (termed the ‘error field’) can drastically alter plasma performance. Improved performance can be achieved using arrays of non-axisymmetric coils to optimize the error field. One metric for evaluating error field control is the locked-mode density limit in Ohmic plasmas, where better compensation allows operation at lower density. Based on this metric, not all coils are equally beneficial for error field control. On DIII-D, the best correction was achieved by using a circular coil (called the ‘n=1 coil’) placed above and off-center to the machine in conjunction with an array of midplane saddle coils (called the ‘C-coil’) [1]. We use recently developed analysis techniques that include the plasma response to examine why this coilset proved so successful on DIII-D. The distinct roles of resonant and non-resonant error fields will be assessed.

[1] J.T. Scoville and R.J. La Haye, *Nucl. Fusion* **43**, 250 (2003).

\*Work supported in part by the US Department of Energy under DE-AC05-06OR23100, DE-FC02-04ER54698 and DE-AC52-07NA27344.