Abstract Submitted for the 56th Annual Meeting Division of Plasma Physics October 27-31, 2014, New Orleans, Louisiana

Category Number and Subject: 6.20 DIII-D Tokamak

[] Theory [X] Experiment

Current Profile Control in DIII-D,* E. Schuster, J.E. Barton, M.D. Boyer, W.P. Wehner, Lehigh University; J.R. Ferron, D.A. Humphreys, A.W. Hyatt, G.L. Jackson, T.C. Luce, M.L. Walker, General Atomics - Experimental results successfully demonstrate the potential of physics-model-based control for systematic attainment of desired g profiles, with the subsequent benefit of enabling exploration and reproducibility. The control scheme is constructed by embedding a nonlinear, control-oriented, physics-based model of the plasma dynamics into the control design process. This modeling approach combines first-principles laws with empirical correlations obtained from physical observations, which leads to PDE models capturing the high-dimensionality and nonlinearity of the plasma response. Model-based control design includes not only the synthesis of feedback controllers for robust regulation or tracking, but also the determination of optimal feedforward actuator trajectories for a systematic approach to scenario planning. Feedforward+feedback (closed loop) control experiments in DIII-D consistently demonstrate improved currentprofile control performance relative to feedforward (open loop) control alone.

*Supported by the US Department of Energy under DE-SC0001334, DE-SC0010661 and DE-FC02-04ER54698.