

Abstract Submitted  
for the DPP97 Meeting of  
The American Physical Society

Sorting Category: 5.1.1.2 (experimental)

**The 110 GHz Gyrotron Installation on DIII-D: Status and Experimental Results**<sup>1</sup> JOHN LOHR, DAN PONCE, R.W. CALLIS, General Atomics, L. POPOV, Gycom, Nizhny Novgorod, Russia, M. ZERBINI, ENEA, Frascati, Italy, P. CAHALAN, CPI, Palo Alto, Ca. — The 110 GHz installation on DIII-D consists of two gyrotrons each of which operates at generated power levels between 0.5 and 1.0 MW for pulse lengths up to 2.0 s. The gyrotrons are connected to DIII-D by windowless evacuated transmission lines. The greatest experience to date has been accumulated with the Gycom Centaur gyrotron, a diode tube which has been operated reliably at generated rf power levels in excess of 0.80 MW for pulse durations of 2.0 s. This tube has been modulated at 100% depth at frequencies up to 1 kHz. The second gyrotron is a Communications and Power Industries model VGT-8011A, a triode geometry, which is in initial testing. For this gyrotron, collector power loading has been measured, the beam steering has been set and pulse/power extension is in progress. DIII-D tests of the system performance are ongoing and initial tokamak experiments on transport, H-mode physics and scaling have begun.

<sup>1</sup>Work supported by U.S. DOE Contract DE-AC03-89ER51114.

Prefer Oral Session  
 Prefer Poster Session

John Lohr  
lohr@gav.gat.com  
General Atomics

Date submitted: July 7, 1997

Electronic form version 1.2