

**Invited Abstract Submitted for the Thirteenth Topical Conference
on Applications of Radio Frequency Power to Plasmas
April 12–14, 1999, Annapolis, Maryland**

Electron Cyclotron Current Drive in DIII-D*

T.C. Luce,[†] General Atomics, P.O. Box 85608, San Diego, California 92186-9784

The localized current generated by electron cyclotron (EC) waves has the potential to sustain optimized profiles of magnetic shear or to suppress instabilities. Experiments to validate off-axis ECCD have been performed on the DIII-D tokamak using up to 1.2 MW of absorbed power at 110 GHz (second harmonic of the electron cyclotron frequency). The minor radius at which the current drive takes place is controlled by adjusting the magnetic field or by changing the poloidal angle of the EC beam. When the deposition is near the axis, the measured EC-driven current is up to 100 kA, and the central safety factor falls more rapidly than in comparable discharges without the ECCD. The current drive efficiency is close to the theoretical value and exhibits the expected linear dependence on the electron temperature T_e . When the EC beam is steered off-axis, currents up to 80 kA are driven, and again the behavior of the profile of the safety factor and the internal inductance are consistent with qualitative expectations for off-axis co-current drive. However, the experiments show that the current drive efficiency, including a normalization to the known temperature dependence, does not decrease over the tested range of 0.1 to 0.5 in normalized minor radius, and substantially more off-axis current is driven than predicted from theoretical calculations. The leading candidate to resolve this discrepancy between theoretical calculations of the off-axis CD efficiency and experimental measurements is finite collisionality. The theoretical treatment of trapping has been based on the assumption that the electrons are collisionless, i.e., that the trapping boundary exists all the way to zero electron energy. This assumption is clearly invalid at electron energies near the thermal velocity which is where the calculations indicate the bulk of the current is driven. Fokker-Planck calculations with finite collisionality are underway to evaluate this effect quantitatively. These measurements of off-axis CD help substantiate the application of ECCD for current profile control in high performance advanced tokamak conditions in DIII-D.

*Work supported by U.S. Department of Energy under Contract Nos. DE-AC03-99ER54463 and W-7405-ENG-38.

[†]In collaboration with Y.R. Lin-Liu, J. Lohr, C.C. Petty, P.A. Politzer, R. Prater, *General Atomics*; R.W. Harvey, *CompX*; G. Giruzzi, *CEA-Centre d'Etudes de Cadarache*, and B.W. Rice, *Lawrence Livermore National Laboratory*.